



TC TrustCenter

TC Enterprise ID Certificate Profiles

TC Enterprise ID
Version 1.8

Hamburg, Germany
April 2011

Geschäftsführung
Austin McCabe
Kristen Laubscher

HRB 96168 AG Hamburg
Ust.-ID-Nr. DE245979558

Bankverbindung
Bank of America
BLZ 50010900
Kto.-Nr. 9160016

IBAN DE14 5001 0900 0019 1600 16
BIC BOFADE33

Sonninstraße 24-28
20097 Hamburg, Germany

Postfach 10 60 49
20041 Hamburg, Germany

Phone: +49 (0)40 / 80 80 26-0

Fax: +49 (0)40 / 80 80 26-1 26

<http://www.trustcenter.de>

Dieses Dokument ist urheberrechtlich geschützt. Die Verwendung der Texte und Abbildungen, auch auszugsweise, ist ohne die schriftliche Zustimmung von TC TrustCenter unzulässig und strafbar. Das gilt insbesondere für Vervielfältigungen, Verbreitungen, Übersetzungen oder die Verwendung in elektronischen Systemen. Ausgenommen hiervon sind das Kopieren und der Ausdruck zum eigenen Gebrauch.

Alle Informationen in diesem Dokument wurden mit größter Sorgfalt erstellt. Weder TC TrustCenter noch der Autor können jedoch für Schäden haftbar gemacht werden, die in Zusammenhang mit der Verwendung dieses Dokumentes stehen.

„TC TrustCenter“, das TC TrustCenter-Logo, „Ident Point“, „TC PKI“ und „TC Info Line“ sind eingetragene Marken der TC TrustCenter GmbH.

Alle in diesem Dokument verwendeten, aber hier nicht genannten Marken- oder Produktnamen sind Marken oder Warenzeichen der entsprechenden Inhaber.

Copyright © 2009 TC TrustCenter GmbH

Alle Rechte vorbehalten.

All rights reserved. No information or images, fully or partially, in any form or by any means, may be reproduced, copied, duplicated, published or used in electronic systems or translations without the prior written consent of TC TrustCenter. This represents a crime, excluding printing and duplicating for one's own use.

All information in this document is compiled with great care. Neither TC TrustCenter nor the author are liable for any damages or disservice, that are in connection with the use of this document.

„TC TrustCenter“, the TC TrustCenter logo, „Ident Point“, „TC PKI“ and „TC Info Line“ are registered trademarks of the TC TrustCenter GmbH.

All brands, product names and trademarks used in this document, but not listed above, are trademarks or service marks of the respective owners.

Copyright © 2009 TC TrustCenter GmbH



Table of Contents

1	Certificate Profiles	5
1.1	“TC Business ID Demo, 30 days”	6
1.2	“SCEP TC Business ID Demo, 30 days”	8
1.3	“TC Business ID Demo, recoverable, 30 days”	10
1.4	“SCEP VPN ID Demo, 30 days”	12
1.5	“TC Client Computer ID Demo, 30 days”	14
1.6	“SCEP TC Client Computer ID Demo, 30 days”	16
1.7	“TC Business ID for Adobe Demo	18
1.8	“TC Trust SSL Demo, 30 days”	20
1.9	“TC Personal ID, 1yr”; 2 yrs or 3 yrs	22
1.10	“TC Business ID, 1yr”; 2 yrs or 3 yrs	24
1.11	“SCEP TC Business ID, 1yr”; 2 yrs or 3 yrs	26
1.12	“TC Business ID, recoverable, 1yr”; 2 yrs or 3 yrs	28
1.13	“TC Business ID, sign+auth, 1yr”; 2 yrs or 3 yrs	30
1.14	“TC Business ID, sign, 1yr”; 2 yrs or 3 yrs	32
1.15	“TC Business ID, auth, 1yr”; 2 yrs or 3 yrs	34
1.16	“TC Business ID, recoverable enc, 1yr”; 2 yrs or 3 yrs	36
1.17	“TC Business ID for Adobe, 1yr”; 2 yrs or 3 yrs	38
1.18	“TC Enrollment Agent ID, 1yr”; 2 yrs or 3 yrs	40
1.19	“TC Domain Controller ID, 1yr”; 2 yrs or 3 yrs	42
1.20	“TC RAS and IAS Server ID, 1yr”; 2 yrs or 3 yrs	44
1.21	“SCEP TC VPN ID, 1yr”; 2 yrs or 3 yrs	46
1.22	“TC Client Computer ID, 1yr”; 2 yrs or 3 yrs	48
1.23	“SCEP TC Client Computer ID, 1yr”; 2 yrs or 3 yrs	50
1.24	“TC Team Certificate, 1yr”; 2yrs or 3yrs	52
1.25	“TC Gateway Certificate, 1yr”; 2yrs or 3yrs	54
1.26	“TC Publisher ID for Adobe AIR, 1yr”; 2yrs or 3yrs	56
1.27	“TC Publisher ID for Microsoft Authenticode, 1yr”; 2yrs or 3yrs	58
1.28	“TC Publisher ID for Java Desktop, 1yr”; 2yrs or 3yrs	60

1 Certificate Profiles

This document describes the certificate hierarchy and the profile of the certificates.

Please note that in the following sections the following fields are always written to refer to the “XI” Sub-CA certificate:

- Issuer
- AuthorityInfoAccess caIssuers URL
- AuthorityInfoAccess OCSP URL
- CRLDistributionPoint

The “XI” has to be replaced by the appropriate roman number depending on the Sub-CA certificate being used.

Note: Not all certificate profiles and not all certificate validity periods are supported by AutoEnrollment or by API enrollment. Please refer to the statement of service document for the list of certificate templates available for AutoEnrollment.

Note: Only certificate profiles starting with *SCEP* are suited for enrollment using the *SCEP* interface.

1.1 “TC Business ID Demo, 30 days”

This certificate profile is to be used for demonstration purposes only. The certificates are chained to the TC Class 1 CA.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 1 L1 CA IX	DirectoryName
	OU	TC TrustCenter Class 1 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 30 days		
Subject	Attribute	Value	Encoding
	CN	<according to GivenName + Surname of the User>	DirectoryName
	OU	<according to Organization Unit of the User>	DirectoryName
	Serial-Number	<according to External ID of the User>	PrintableString
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature nonRepudiation keyEncipherment dataEncipherment
extKeyUsage	no	clientAuth (1.3.6.1.5.5.7.3.2) MS SmartCardLogon (1.3.6.1.4.1.311.20.2.2) emailProtection (1.3.6.1.5.5.7.3.4) IPsec User (1.3.6.1.5.5.7.3.7)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.1 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	Other Name / UPN (1.3.6.1.4.1.311.20.2.3) = <Windows User Login Name (User Principal Name)> rfc822-Name = <Email Address>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: calssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class1_L1_CA_IX.crt accessMethod: ocsp accessLocation: URL= http://ocsp.IX.tcclass1.tcuniversal-i.trustcenter.de
cRLDistributionPoints	no	http://crl.IX.tcclass1.tcuniversal-i.trustcenter.de/crl/v2/tc_class1_L1_CA_IX.crl
certificateTemplate-Information	no	Extension is only present if AutoEnrollment has been used to request the certificate. Template OID= 1.2.276.0.44.5.1.13.1.1 Version=<according to current configuration, e.g. 100.1>



1.2 “SCEP TC Business ID Demo, 30 days”

This certificate profile is to be used for demonstration purposes only. The certificates are chained to the TC Class 1 CA. All certificate profiles beginning with SCEP are intended for SCEP enrollment only.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 1 L1 CA IX	DirectoryName
	OU	TC TrustCenter Class 1 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 30 days		
Subject	Attribute	Value	Encoding
	CN	<according to GivenName + Surname of the User>	DirectoryName
	OU	<according to Organization Unit of the User>	DirectoryName
	Serial-Number	<according to External ID of the User>	PrintableString
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature nonRepudiation keyEncipherment dataEncipherment
extKeyUsage	no	clientAuth (1.3.6.1.5.5.7.3.2) MS SmartCardLogon (1.3.6.1.4.1.311.20.2.2) emailProtection (1.3.6.1.5.5.7.3.4) IPsec User (1.3.6.1.5.5.7.3.7)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.1 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	Other Name / UPN (1.3.6.1.4.1.311.20.2.3) = <Windows User Login Name (User Principal Name)> rfc822-Name = <Email Address>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: calssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class1_L1_CA_IX.crt accessMethod: ocsp accessLocation: URL= http://ocsp.IX.tcclass1.tcuniversal-i.trustcenter.de
cRLDistributionPoints	no	http://crl.IX.tcclass1.tcuniversal-i.trustcenter.de/crl/v2/tc_class1_L1_CA_IX.crl

1.3 “TC Business ID Demo, recoverable, 30 days”

This certificate profile is to be used for demonstration purposes only. The certificates are chained to the TC Class 1 CA.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 1 L1 CA IX	DirectoryName
	OU	TC TrustCenter Class 1 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 30 days		
Subject	Attribute	Value	Encoding
	CN	<according to GivenName + Surname of the User>	DirectoryName
	OU	<according to Organization Unit of the User>	DirectoryName
	Serial-Number	<according to External ID of the User>	PrintableString
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	2048 bit RSA		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature nonRepudiation keyEncipherment dataEncipherment
extKeyUsage	no	clientAuth (1.3.6.1.5.5.7.3.2) MS SmartCardLogon (1.3.6.1.4.1.311.20.2.2) emailProtection (1.3.6.1.5.5.7.3.4) IPsec User (1.3.6.1.5.5.7.3.7)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.1 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	Other Name / UPN (1.3.6.1.4.1.311.20.2.3) = <Windows User Login Name (User Principal Name)> rfc822-Name = <Email Address>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: calssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class1_L1_CA_IX.crt accessMethod: ocsp accessLocation: URL= http://ocsp.IX.tcclass1.tcuniversal-i.trustcenter.de
cRLDistributionPoints	no	http://crl.IX.tcclass1.tcuniversal-i.trustcenter.de/crl/v2/tc_class1_L1_CA_IX.crl
certificateTemplate-Information	no	Extension is only present if AutoEnrollment has been used to request the certificate. Template OID= 1.2.276.0.44.5.1.13.2.1 Version=<according to current configuration, e.g. 100.1>

1.4 “SCEP VPN ID Demo, 30 days”

This certificate profile is to be used for demonstration purposes only. The certificates are chained to the TC Class 0 Root. This root certificate is not pre-installed in popular web browsers and can be downloaded from the TC TrustCenter [homepage](#). All certificate profiles beginning with *SCEP* are intended for *SCEP* enrollment only.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	Email	certificate@trustcenter.de	IA5String
	OU	TC TrustCenter Class 0 CA	DirectoryName
	O	TC TrustCenter AG	DirectoryName
	L	Hamburg	DirectoryName
	SP	Hamburg	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 30 days		
Subject	Attribute	Value	Encoding
	CN	<FQDN of network device as specified in the request>	DirectoryName
	OU	<as specified in request>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
	DC	<as specified in request>	IA5String
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature keyEncipherment
extKeyUsage	no	1.3.6.1.5.5.7.3.1 (Server Authentication) 1.3.6.1.5.5.7.3.2 (Client Authentication) 1.3.6.1.5.5.8.2.2 (iKEIntermediate)
netscapeCertificate Type	no	SSL-Client Authentication SSL-Server-Authentication
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.0 cPSuri = http://www.trustcenter.de/guidelines
authorityInfoAccess	no	accessMethod: caIssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tcclass0.crt accessMethod: ocsp accessLocation: URL= http://ocsp.tcclass0.trustcenter.de
cRLDistributionPoints	no	http://www.trustcenter.de/crl/v2/tcclass0.crl

1.5 “TC Client Computer ID Demo, 30 days”

This certificate profile is to be used for demonstration purposes only. The certificates are chained to the TC Class 1 CA.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 1 L1 CA IX	DirectoryName
	OU	TC TrustCenter Class 1 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 30 days		
Subject	Attribute	Value	Encoding
	CN	Name of client computer	DirectoryName
	OU	<as specified in request>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
	DC	<as specified in request>	IA5String
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	Digital Signature, Key Encipherment
extKeyUsage	no	1.3.6.1.5.5.7.3.2 (Client Authentication)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.1 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	DNS-Name=<FQDN as specified in request>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: caIssuers accessLocation: URL=http://www.trustcenter.de/certservices/cacerts/tc_class1_L1_CA_IX.crt accessMethod: ocsp accessLocation: URL=http://ocsp.IX.tcclass1.tcuniversal-i.trustcenter.de
cRLDistributionPoints	no	http://crl.IX.tcclass1.tcuniversal-i.trustcenter.de/crl/v2/tc_class1_L1_CA_IX.crl
certificateTemplate-Information	no	Extension is only present if AutoEnrollment has been used to request the certificate. Template OID= 1.2.276.0.44.5.1.18.1.0 Version=<according to current configuration, e.g. 100.1>

1.6 “SCEP TC Client Computer ID Demo, 30 days”

This certificate profile is to be used for demonstration purposes only. The certificates are chained to the TC Class 1 CA. All certificate profiles beginning with *SCEP* are intended for *SCEP* enrollment only.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 1 L1 CA IX	DirectoryName
	OU	TC TrustCenter Class 1 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 30 days		
Subject	Attribute	Value	Encoding
	CN	Name of client computer	DirectoryName
	OU	<as specified in request>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
	DC	<as specified in request>	IA5String
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	Digital Signature, Key Encipherment
extKeyUsage	no	1.3.6.1.5.5.7.3.2 (Client Authentication)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.1 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	DNS-Name=<FQDN as specified in request>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: caIssuers accessLocation: URL=http://www.trustcenter.de/certservices/cacerts/tc_class1_L1_CA_IX.crt accessMethod: ocsp accessLocation: URL=http://ocsp.IX.tcclass1.tcuniversal-i.trustcenter.de
cRLDistributionPoints	no	http://crl.IX.tcclass1.tcuniversal-i.trustcenter.de/crl/v2/tc_class1_L1_CA_IX.crl

1.7 “TC Business ID for Adobe Demo

This certificate profile is to be used for demonstration purposes only. The certificates are chained to the CDS Root. A flag in the certificate causes a warning message box to appear whenever a PDF signed with this certificate is being opened.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter CA for Adobe I	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 30 days		
Subject	Attribute	Value	Encoding
	CN	TEST	PrintableString
	OU	<according to Organization Unit of the User>	DirectoryName
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	2048 bit RSA		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	Non-repudiation, digital signature
extKeyUsage	no	PDF Signature (1.2.840.113583.1.1.5)
certificatePolicies	no	[1] Policy-OID 1.2.840.113583.1.2.2 cPSuri = http://www.trustcenter.de/cps
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: ocsf accessLocation: URL= http://ocsp.l.adobe-cds.trustcenter.de
cRLDistributionPoints	no	http://www.trustcenter.de/crl/v2/tc_ca_for_adobe_l.crl
Archive Revocation Info	no	True
TimeStamp URL	no	tss.l.adobe-cds.trustcenter.de

1.8 “TC Trust SSL Demo, 30 days”

This certificate profile is to be used for demonstration purposes only. The certificates are chained to the TC Class 0 Root. This root certificate is not pre-installed in popular web browsers and can be downloaded from the TC TrustCenter [homepage](#).

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	Email	certificate@trustcenter.de	IA5String
	OU	TC TrustCenter Class 0 CA	DirectoryName
	O	TC TrustCenter AG	DirectoryName
	L	Hamburg	DirectoryName
	SP	Hamburg	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 30 days		
Subject	Attribute	Value	Encoding
	CN	<FQDN of the SSL server as specified in request>	DirectoryName
	OU	<as specified in request>	DirectoryName
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature nonRepudiation keyEncipherment dataEncipherment
extKeyUsage	no	1.3.6.1.5.5.7.3.1 (Server Authentication) 1.3.6.1.5.5.7.3.2 (Client Authentication)
netscapeCertificateType	no	SSL-Client Authentication SSL-Server-Authentication
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.0 cPSuri = http://www.trustcenter.de/guidelines
authorityInfoAccess	no	accessMethod: caIssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tcclass0.crt accessMethod: ocsp accessLocation: URL= http://ocsp.tcclass0.trustcenter.de
cRLDistributionPoints	no	http://www.trustcenter.de/crl/v2/tcclass0.crl
certificateTemplate-Information	no	Extension is only present if AutoEnrollment has been used to request the certificate. Template OID= 1.2.276.0.44.5.1.16.1 Version=<according to current configuration, e.g. 100.1>

1.9 “TC Personal ID, 1yr”; 2 yrs or 3 yrs

This certificate profile is to be used for real applications. The certificates are chained to the TC Class 1 CA. The certificate will have no Organization-field in the subject-DN, they are intended for external partners or contractors.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 1 L1 CA IX	DirectoryName
	OU	TC TrustCenter Class 1 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	<according to GivenName + Surname of the User>	DirectoryName
	OU	<according to Organization Unit of the User>	DirectoryName
	Serial-Number	<according to External ID of the User>	PrintableString
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature nonRepudiation keyEncipherment dataEncipherment
extKeyUsage	no	clientAuth (1.3.6.1.5.5.7.3.2) MS SmartCardLogon (1.3.6.1.4.1.311.20.2.2) emailProtection (1.3.6.1.5.5.7.3.4) IPsec User (1.3.6.1.5.5.7.3.7)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.1 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	Other Name / UPN (1.3.6.1.4.1.311.20.2.3) = <Windows User Login Name (User Principal Name)> rfc822-Name = <Email Address>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: calssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class1_L1_CA_IX.crt accessMethod: ocsp accessLocation: URL= http://ocsp.IX.tcclass1.tcuniversal-i.trustcenter.de
cRLDistributionPoints	no	http://crl.IX.tcclass1.tcuniversal-i.trustcenter.de/crl/v2/tc_class1_L1_CA_IX.crl
certificateTemplate-Information	no	Extension is only present if AutoEnrollment has been used to request the certificate. Template OID= 1.2.276.0.44.5.1.12.1.1 append ".2" or ".3" in case of 2 or 3 years validity Version=<according to current configuration, e.g. 100.1>

1.10 “TC Business ID, 1yr”; 2 yrs or 3 yrs

This certificate profile is to be used for real applications. It is not recoverable. The certificates are chained to the TC Class 2 Root.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XI	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	<according to GivenName + Surname of the User>	DirectoryName
	OU	<according to Organization Unit of the User>	DirectoryName
	Serial-Number	<according to External ID of the User>	PrintableString
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature nonRepudiation keyEncipherment dataEncipherment
extKeyUsage	no	clientAuth (1.3.6.1.5.5.7.3.2) MS SmartCardLogon (1.3.6.1.4.1.311.20.2.2) emailProtection (1.3.6.1.5.5.7.3.4) IPsec User (1.3.6.1.5.5.7.3.7)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	Other Name / UPN (1.3.6.1.4.1.311.20.2.3) = <Windows User Login Name (User Principal Name)> rfc822-Name = <Email Address>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: calssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XI.crt accessMethod: ocsp accessLocation: URL= http://ocsp.XI.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XI.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XI.crl
certificateTemplate-Information	no	Extension is only present if AutoEnrollment has been used to request the certificate. Template OID= 1.2.276.0.44.5.1.13.3.1 append ".2" or ".3" in case of 2 or 3 years validity Version=<according to current configuration, e.g. 100.1>



1.11 “SCEP TC Business ID, 1yr”; 2 yrs or 3 yrs

This certificate profile is to be used for real applications. It is not recoverable. The certificates are chained to the TC Class 2 Root. All certificate profiles beginning with *SCEP* are intended for *SCEP* enrollment only.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XI	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	<according to GivenName + Surname of the User>	DirectoryName
	OU	<according to Organization Unit of the User>	DirectoryName
	Serial-Number	<according to External ID of the User>	PrintableString
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature nonRepudiation keyEncipherment dataEncipherment
extKeyUsage	no	clientAuth (1.3.6.1.5.5.7.3.2) MS SmartCardLogon (1.3.6.1.4.1.311.20.2.2) emailProtection (1.3.6.1.5.5.7.3.4) IPsec User (1.3.6.1.5.5.7.3.7)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	Other Name / UPN (1.3.6.1.4.1.311.20.2.3) = <Windows User Login Name (User Principal Name)> rfc822-Name = <Email Address>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: calssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XI.crt accessMethod: ocsp accessLocation: URL= http://ocsp.XI.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XI.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XI.crl

1.12 “TC Business ID, recoverable, 1yr”; 2 yrs or 3 yrs

This certificate profile is to be used for real applications. The certificates are chained to the TC Class 2 Root.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XI	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	<according to GivenName + Surname of the User>	DirectoryName
	OU	<according to Organization Unit of the User>	DirectoryName
	Serial-Number	<according to External ID of the User>	PrintableString
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	2048 bit RSA		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature nonRepudiation keyEncipherment dataEncipherment
extKeyUsage	no	clientAuth (1.3.6.1.5.5.7.3.2) MS SmartCardLogon (1.3.6.1.4.1.311.20.2.2) emailProtection (1.3.6.1.5.5.7.3.4) IPsec User (1.3.6.1.5.5.7.3.7)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	Other Name / UPN (1.3.6.1.4.1.311.20.2.3) = <Windows User Login Name (User Principal Name)> rfc822-Name = <Email Address>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: calssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XI.crt accessMethod: ocsp accessLocation: URL= http://ocsp.XI.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XI.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XI.crl
certificateTemplate-Information	no	Extension is only present if AutoEnrollment has been used to request the certificate. Template OID= 1.2.276.0.44.5.1.13.4.1 append ".2" or ".3" in case of 2 or 3 years validity Version=<according to current configuration, e.g. 100.1>

1.13 “TC Business ID, sign+auth, 1yr”; 2 yrs or 3 yrs

This certificate profile is to be used for signature and authentication applications. The certificates are chained to the TC Class 2 Root.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XI	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	<according to GivenName + Surname of the User>	DirectoryName
	OU	<according to Organization Unit of the User>	DirectoryName
	Serial-Number	<according to External ID of the User>	PrintableString
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature nonRepudiation
extKeyUsage	no	clientAuth (1.3.6.1.5.5.7.3.2) MS SmartCardLogon (1.3.6.1.4.1.311.20.2.2) emailProtection (1.3.6.1.5.5.7.3.4) IPsec User (1.3.6.1.5.5.7.3.7)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	Other Name / UPN (1.3.6.1.4.1.311.20.2.3) = <Windows User Login Name (User Principal Name)> rfc822-Name = <Email Address>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: calssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XI.crt accessMethod: ocsp accessLocation: URL= http://ocsp.XI.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XI.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XI.crl
certificateTemplateInformation	no	Extension is only present if AutoEnrollment has been used to request the certificate. Template OID= 1.2.276.0.44.5.1.13.3.2 append “.2” or “.3” in case of 2 or 3 years validity Version=<according to current configuration, e.g. 100.1>

1.14 “TC Business ID, sign, 1yr”; 2 yrs or 3 yrs

This certificate profile is to be used for signature applications. The certificates are chained to the TC Class 2 Root.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XI	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	<according to GivenName + Surname of the User>	DirectoryName
	OU	<according to Organization Unit of the User>	DirectoryName
	Serial-Number	<according to External ID of the User>	PrintableString
	O	<according to Organization of the affiliate associated with the requesting user >	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature nonRepudiation
extKeyUsage	no	emailProtection (1.3.6.1.5.5.7.3.4)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	Other Name / UPN (1.3.6.1.4.1.311.20.2.3) = <Windows User Login Name (User Principal Name)> rfc822-Name = <Email Address>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: caIssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XI.crt accessMethod: ocsp accessLocation: URL= http://ocsp.XI.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XI.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XI.crl
certificateTemplate-Information	no	Extension is only present if AutoEnrollment has been used to request the certificate. Template OID= 1.2.276.0.44.5.1.13.3.4 append “.2” or “.3” in case of 2 or 3 years validity Version=<according to current configuration, e.g. 100.1>

1.15 “TC Business ID, auth, 1yr”; 2 yrs or 3 yrs

This certificate profile is to be used for authentication applications. The certificates are chained to the TC Class 2 Root.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XI	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	<according to GivenName + Surname of the User>	DirectoryName
	OU	<according to Organization Unit of the User>	DirectoryName
	Serial-Number	<according to External ID of the User>	PrintableString
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature
extKeyUsage	no	clientAuth (1.3.6.1.5.5.7.3.2) MS SmartCardLogon (1.3.6.1.4.1.311.20.2.2) IPsec User (1.3.6.1.5.5.7.3.7)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	Other Name / UPN (1.3.6.1.4.1.311.20.2.3) = <Windows User Login Name (User Principal Name)> rfc822-Name = <Email Address>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: calssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XI.crt accessMethod: ocsp accessLocation: URL= http://ocsp.XI.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XI.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XI.crl
certificateTemplateInformation	no	Extension is only present if AutoEnrollment has been used to request the certificate. Template OID= 1.2.276.0.44.5.1.13.3.5 append ".2" or ".3" in case of 2 or 3 years validity Version=<according to current configuration, e.g. 100.1>

1.16 “TC Business ID, recoverable enc, 1yr”; 2 yrs or 3 yrs

This certificate profile is to be used for encryption and decryption applications, e.g. email encryption. The certificates are chained to the TC Class 2 Root.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XI	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	<according to GivenName + Surname of the User>	DirectoryName
	OU	<according to Organization Unit of the User>	DirectoryName
	Serial-Number	<according to External ID of the User>	PrintableString
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	2048 bit RSA		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	keyEncipherment, dataEncipherment
extKeyUsage	no	emailProtection (1.3.6.1.5.5.7.3.4) Encrypting File System (1.3.6.1.4.1.311.10.3.4)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	rfc822-Name = <Email Address>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: caIssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XI.crt accessMethod: ocsp accessLocation: URL= http://ocsp.XI.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XI.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XI.crl
certificateTemplateInformation	no	Extension is only present if AutoEnrollment has been used to request the certificate. Template OID= 1.2.276.0.44.5.1.13.4.3 append ".2" or ".3" in case of 2 or 3 years validity Version=<according to current configuration, e.g. 100.1>

1.17 “TC Business ID for Adobe, 1yr”; 2 yrs or 3 yrs

This certificate profile is to be used for PDF signature only. The certificates are chained to the CDS Root.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter CA for Adobe I	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	<according to GivenName + Surname of the User>	DirectoryName
	OU	<according to Organization Unit of the User>	DirectoryName
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	2048 bit RSA		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	Non-repudiation, digital signature
extKeyUsage	no	PDF Signature (1.2.840.113583.1.1.5)
certificatePolicies	no	[1] Policy-OID 1.2.840.113583.1.2.1 cPSuri = http://www.trustcenter.de/cps
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: ocs accessLocation: URL= http://ocsp.l.adobe-cds.trustcenter.de
cRLDistributionPoints	no	http://www.trustcenter.de/crl/v2/tc_ca_for_adobe_l.crl
Archive Revocation Info	no	True
TimeStamp URL	no	tss.l.adobe-cds.trustcenter.de

1.18 “TC Enrollment Agent ID, 1yr”; 2 yrs or 3 yrs

This certificate profile is to be used for enrollment agents. The certificates are chained to the TC Class 2 Root.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XI	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	<according to GivenName + Surname of the User>	DirectoryName
	OU	<according to Organization Unit of the User>	DirectoryName
	Serial-Number	<according to External ID of the User>	PrintableString
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature nonRepudiation keyEncipherment dataEncipherment
extKeyUsage	no	clientAuth (1.3.6.1.5.5.7.3.2) MS SmartCardLogon (1.3.6.1.4.1.311.20.2.2) emailProtection (1.3.6.1.5.5.7.3.4) IPsec User (1.3.6.1.5.5.7.3.7) Certificate Request Agent (1.3.6.1.4.1.311.20.2.1)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	Other Name / UPN (1.3.6.1.4.1.311.20.2.3) = <Windows User Login Name (User Principal Name)> rfc822-Name = <Email Address>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: calssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XI.crt accessMethod: ocsp accessLocation: URL= http://ocsp.XI.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XI.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XI.crl
certificateTemplate-Information	no	Extension is only present if AutoEnrollment has been used to request the certificate. Template OID= 1.2.276.0.44.5.1.14.1.1 append ".2" or ".3" in case of 2 or 3 years validity Version=<according to current configuration, e.g. 100.1>

1.19 “TC Domain Controller ID, 1yr”; 2 yrs or 3 yrs

In order to setup smart card logon the domain controller must be equipped with this type of certificate.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XI	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	Name of domain controller	DirectoryName
	OU	<as specified>	DirectoryName
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
	DC	<as specified in request>	IA5String
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	Digital Signature, Key Encipherment
extKeyUsage	no	1.3.6.1.5.5.7.3.1 (Server Authentication) 1.3.6.1.5.5.7.3.2 (Client Authentication) 1.3.6.1.4.1.311.20.2.2 (Smart Card Logon)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	DNS-Name=<FQDN as specified in request> RFC822-Name=<as specified in request> GUID[1.3.6.1.4.1.311.25.1] = <as specified in request>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: calssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XI.crt accessMethod: ocsp accessLocation: URL= http://ocsp.XI.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XI.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XI.crl
certificateTemplate-Information	no	TemplateName (1.3.6.1.4.1.311.20.2) = „DomainController“ (BMPString)
certificateTemplate-Information	no	Extension is only present if AutoEnrollment has been used to request the certificate. Template OID= 1.2.276.0.44.5.1.17.1 append “.2” or “.3” in case of 2 or 3 years validity Version=<according to current configuration, e.g. 100.1>

1.20 “TC RAS and IAS Server ID, 1yr”; 2 yrs or 3 yrs

This certificate is intended for IAS and RAS servers.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XI	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	Name of RAS and IAS server	DirectoryName
	OU	<as specified>	DirectoryName
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
	DC	<as specified in request>	IA5String
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	Digital Signature, Key Encipherment
extKeyUsage	no	1.3.6.1.5.5.7.3.1 (Server Authentication) 1.3.6.1.5.5.7.3.2 (Client Authentication) 1.3.6.1.5.5.8.2.2 (iKEIntermediate)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	DNS-Name=<FQDN as specified in request>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: caIssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XI.crt accessMethod: ocsp accessLocation: URL= http://ocsp.XI.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XI.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XI.crl
certificateTemplateInformation	no	Extension is only present if AutoEnrollment has been used to request the certificate. Template OID= 1.2.276.0.44.5.1.17.2 append ".2" or ".3" in case of 2 or 3 years validity Version=<according to current configuration, e.g. 100.1>

1.21 “SCEP TC VPN ID, 1yr”; 2 yrs or 3 yrs

This certificate is intended for network devices. All certificate profiles beginning with *SCEP* are intended for *SCEP* enrollment only.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XI	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	<FQDN of network device as specified in the request>	DirectoryName
	OU	<as specified>	DirectoryName
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
	DC	<as specified in request>	IA5String
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature keyEncipherment
extKeyUsage	no	1.3.6.1.5.5.7.3.1 (Server Authentication) 1.3.6.1.5.5.7.3.2 (Client Authentication) 1.3.6.1.5.5.8.2.2 (iKEIntermediate)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	DNS-Name=<FQDN as specified in request>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: caIssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XI.crt accessMethod: ocsp accessLocation: URL= http://ocsp.XI.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XI.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XI.crl

1.22 “TC Client Computer ID, 1yr”; 2 yrs or 3 yrs

This certificate is intended to be used for machine authentication.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XI	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	Name of client computer	DirectoryName
	OU	<as specified in request>	DirectoryName
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	Digital Signature, Key Encipherment
extKeyUsage	no	1.3.6.1.5.5.7.3.2 (Client Authentication)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	DNS-Name=<FQDN as specified in request>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: caIssuers accessLocation: URL=http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XI.crt accessMethod: ocsp accessLocation: URL=http://ocsp.XI.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XI.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XI.crl
certificateTemplate-Information	no	Extension is only present if AutoEnrollment has been used to request the certificate. Template OID= 1.2.276.0.44.5.1.18.1 append “.2” or “.3” in case of 2 or 3 years validity Version=<according to current configuration, e.g. 100.1>

1.23 “SCEP TC Client Computer ID, 1yr”; 2 yrs or 3 yrs

This certificate is intended to be used for machine authentication. All certificate profiles beginning with *SCEP* are intended for *SCEP* enrollment only.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XI	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	Name of client computer	DirectoryName
	OU	<as specified in request>	DirectoryName
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
	DC	<as specified in request>	IA5String
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	Digital Signature, Key Encipherment
extKeyUsage	no	1.3.6.1.5.5.7.3.2 (Client Authentication)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	DNS-Name=<FQDN as specified in request>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: caIssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XI.crt accessMethod: ocsp accessLocation: URL= http://ocsp.XI.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XI.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XI.crl

1.24 “TC Team Certificate, 1yr”; 2yrs or 3yrs

Team certificates are intended to be shared among several members of a team as opposed to be exclusively used by the “Certificate Owner” like the TC Business ID.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XI	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	<Team name according to request> + “Team Certificate”	DirectoryName
	OU	<as specified in request>	DirectoryName
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature nonRepudiation keyEncipherment dataEncipherment
extKeyUsage	no	clientAuth (1.3.6.1.5.5.7.3.2) emailProtection (1.3.6.1.5.5.7.3.4) IPsec User (1.3.6.1.5.5.7.3.7)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	rfc822-Name = <Email Address>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: calssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XI.crt accessMethod: ocsp accessLocation: URL= http://ocsp.XI.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XI.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XI.crl
certificateTemplate-Information	no	Extension is only present if AutoEnrollment has been used to request the certificate. Template OID= 1.2.276.0.44.5.1.15.1.1 append ".2" or ".3" in case of 2 or 3 years validity Version=<according to current configuration, e.g. 100.1>

1.25 “TC Gateway Certificate, 1yr”; 2yrs or 3yrs

Gateway certificates are intended to be used by E-Mail gateways or the Microsoft System Center Configuration Manager. The following function names are approved:

- "Secure Mail Gateway"
- "E-mail Gateway"
- "Automatic Mail Signature " or "Automatische Mail Signatur"
- "Mail Encryption" or "Mailverschlüsselung"
- "Archive Services" or "Archivservice"
- "The site code of this site server is <XXX>"

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XI	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	<approved function name as specified in the request>	DirectoryName
	OU	<as specified in request>	DirectoryName
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	<according to certificate request>		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature keyEncipherment dataEncipherment
extKeyUsage	no	emailProtection (1.3.6.1.5.5.7.3.4) documentSigning (1.3.6.1.4.1.311.10.3.12)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines
subjectAltNames	no	rfc822-Name = <Email Address>
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: caIssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XI.crt accessMethod: ocsp accessLocation: URL= http://ocsp.XI.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XI.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XI.crl
certificateTemplate-Information	no	Extension is only present if AutoEnrollment has been used to request the certificate. Template OID= 1.2.276.0.44.5.1.21.1.1 replace ".1" by ".2" or ".3" in case of 2 or 3 years validity Version=<according to current configuration, e.g. 100.1>

1.26 “TC Publisher ID for Adobe AIR, 1yr”; 2yrs or 3yrs

Certificate for signing Adobe AIR code.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XII	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	OU	<according to Organization Unit of the User>	DirectoryName
	OU	TC Publisher ID for <application name, e.g. Adobe AIR>	DirectoryName
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	<according to certificate request>, at least 2048 bit RSA key length!		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature
extKeyUsage	no	codeSigning (1.3.6.1.5.5.7.3.3)
nsCertType	no	Code-Signatur (10)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines [2] Policy-OID 1.2.276.0.44.1.1.1.2.2.3.1
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: caIssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XII.crt accessMethod: ocsp accessLocation: URL= http://ocsp.XII.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XII.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XII.crl

1.27 “TC Publisher ID for Microsoft Authenticode, 1yr”; 2yrs or 3yrs

Certificate for Microsoft Authenticode.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XII	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	OU	<according to Organization Unit of the User>	DirectoryName
	OU	TC Publisher ID for Authenticode	DirectoryName
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	<according to certificate request>, at least 2048 bit RSA key length		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature nonRepudiation
extKeyUsage	no	codeSigning (1.3.6.1.5.5.7.3.3) Kernel Mode Code Signing (1.3.6.1.4.1.311.61.1.1)
nsCertType	no	Code-Signatur (10)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines [2] Policy-OID 1.2.276.0.44.1.1.1.2.2.1.1
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: caIssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XII.crt accessMethod: ocsp accessLocation: URL= http://ocsp.XII.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XII.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XII.crl

1.28 “TC Publisher ID for Java Desktop, 1yr”; 2yrs or 3yrs

Certificate for signing Java code for desktop applications.

Data Field	Value		
Version	v3		
Serial Number	[Automatic number according to TC TrustCenter standard]		
Signature Algorithm	sha1withRSAEncryption		
Issuer	Attribute	Value	Encoding
	CN	TC TrustCenter Class 2 L1 CA XII	DirectoryName
	OU	TC TrustCenter Class 2 L1 CA	DirectoryName
	O	TC TrustCenter GmbH	DirectoryName
	C	DE	PrintableString
Validity	[Date of Issuance] + 1, 2 or 3 years		
Subject	Attribute	Value	Encoding
	CN	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	OU	<according to Organization Unit of the User>	DirectoryName
	OU	TC Publisher ID for Java Desktop	DirectoryName
	O	<according to Organization of the affiliate associated with the requesting user>	DirectoryName
	L	<according to Location of the affiliate associated with the requesting user>	DirectoryName
	SP	<according to State of the affiliate associated with the requesting user>	DirectoryName
	C	<according to Country of the affiliate associated with the requesting user>	PrintableString
Subject Public Key	<according to certificate request>, at least 2048 bit RSA key length		

Extension	Crit.	Value
basicConstraints	yes	cA: FALSE
keyUsage	yes	digitalSignature nonRepudiation
extKeyUsage	no	codeSigning (1.3.6.1.5.5.7.3.3)
nsCertType	no	Code-Signatur (10)
certificatePolicies	no	[1] Policy-OID 1.2.276.0.44.1.1.1.2 cPSuri = http://www.trustcenter.de/guidelines [2] Policy-OID 1.2.276.0.44.1.1.1.2.2.2.1
subjectKeyIdentifier	no	[Key-ID of this Certificate]
authorityKeyIdentifier	no	[Key-ID of Issuer Certificate]
authorityInfoAccess	no	accessMethod: caIssuers accessLocation: URL= http://www.trustcenter.de/certservices/cacerts/tc_class2_L1_CA_XII.crt accessMethod: ocsp accessLocation: URL= http://ocsp.XII.tcclass2-ii.trustcenter.de
cRLDistributionPoints	no	http://crl.XII.tcclass2-ii.trustcenter.de/crl/v2/tc_class2_L1_CA_XII.crl